





STANDARD FEATURES ORCA® Hypalon or PVC tube Welded seams (PVC)

Flush mount non-return valves

High tensile chromated & powder coated aluminum hull

Bow locker (Fit 24L fuel tank)
Integrated transom supports

Removable seat

Bow cushion
Lifting points and towing eyes

Tow bridle points Brushed foam teak finish deck

Heavy duty rubbing strake Full length keel guard

Tank strap kit

Under seat bag Highfield dry bag

Foot pump, oars, repair kit

## **OPTIONAL EXTRAS**

FRP/Nylon Bow Step Molded bow cleat Boat cover

## (OLOVR SCHEMES



HIGHFIELD

OVERALL LENGTH	360cm	11′10″
INTERNAL LENGTH	267cm	8′9″
OVERALL WIDTH	170cm	5′7″
INTERNAL WIDTH	79cm	2′7″
DEADRISE	15°	
TUBE DIAMETER	44cm	17"
NUMBER OF AIR CHAMBERS	3	
MAXIMUM LOAD	561 kg	1237lbs
MAXIMUM PEOPLE	6	
BOAT WEIGHT*	75kg	165lbs
MAXIMUM POWER	30hp	
ENGINE SHAFT	S	
DESIGN CATEGORY	С	

\* boat only



