



STANDARD FEATURES
ORCA® Hypalon or PVC tube
Welded seams (PVC)
Flush mount non-return valves High tensile chromated & powdercoated aluminum hull Bow locker (Fit 24L fuel tank) Integrated transom supports Removable seat Bow cushion Lifting points and towing eyes
Tow bridle points Brushed foam teak finish deck Heavy duty rubbing strake Full length keel guard Tank strap kit Under seat bag Highfield dry bag Foot pump, oars, repair kit

OPTIONAL EXTRAS

FRP/Nylon Bow Step Molded bow cleat

(OLOVR SCHEMES



| OVERALL LENGTH | 396cm | 13′ |
|------------------------|-------|---------|
| INTERNAL LENGTH | 291cm | 9′6″ |
| OVERALL WIDTH | 197cm | 6′5″ |
| INTERNAL WIDTH | 91cm | 3′1″ |
| DEADRISE | 20° | |
| TUBE DIAMETER | 47cm | 18.5″ |
| NUMBER OF AIR CHAMBERS | 4 | |
| MAXIMUM LOAD | 878kg | 1936lbs |
| MAXIMUM PEOPLE | 8 | |
| BOAT WEIGHT* | 147kg | 324lbs |
| MAXIMUM POWER | 50hp | |
| ENGINE SHAFT | S | |

* boat only

