





- ORCA® Hypalon or PVC tube Welded seams (PVC)

- Flush mount non-return valves
- High tensile chromated & powder coated aluminum hull

- Integrated transom supportsSelf-draining deckIntegrated under-deck fuel tank
- Lifting points and towing eyes
- Tow bridle points
- Anti-slip deck - Heavy duty rubbing strake
- Keel guard
- Highfield dry bag
- Foot pump, oars, repair kit
- Carbon dash
- Bow cushion
- Electrical pack for console Electrical pack for boat

OPTIONAL EXTRAS

- Console & seat options
- Rollbar Dive rack
- T-Top / XL T-Top
- Brushed foam teak finish deck
- Roll bar with ladder



OVERALL LENGTH	760cm 25′		
INTERNAL LENGTH	590cm 19′4″		
OVERALL WIDTH	288cm	9'6''	
INTERNAL WIDTH	169cm	5′7′′	
DEADRISE	26°		
TUBE DIAMETER	58cm	23′′	
NUMBER OF AIR CHAMBERS	6		
	•		
MAXIMUM LOAD	1753kg	3865lbs	
MAXIMUM LOAD MAXIMUM PEOPLE		3865lbs	
	1753kg	3865lbs	
MAXIMUM PEOPLE	1753kg 1	3865lbs 6 2161lbs	
MAXIMUM PEOPLE BOAT WEIGHT*	1753kg 1 980kg	3865lbs 6 2161lbs Ohp	

01.01/R	(CHFMF(

•			, <u>~</u>	HVLL
			K-	TVBE
			~	UPHOLSTER:

OVERALL LENGTH	760cm 25′		
NTERNAL LENGTH	590cm 19′4″		
OVERALL WIDTH	288cm	9′6′′	
NTERNAL WIDTH	169cm	5′7′′	
EADRISE	26°		
UBE DIAMETER	58cm	23′′	
NUMBER OF AIR CHAMBERS	6		
MAXIMUM LOAD	1753kg	3865lbs	
MAXIMUM PEOPLE	16		
OAT WEIGHT*	980kg	2161lbs	
MAXIMUM POWER	300hp		
NGINE SHAFT	XL		
UEL TANK	2851		
ESIGN CATEGORY	C or B		

