CLASSIC 260 & 290

 \bigcirc



STANDARD FEATURES

ORCA® Hypalon or PVC tube Welded seams (PVC) Flush mount non-return valves High tensile chromated & powder coated aluminum hull Bow locker (Fit 24L fuel tank) Integrated transom supports Removable seat Lifting points and towing eyes Tow bridle points Brushed foam teak finish deck Heavy duty rubbing strake Full length keel guard Tank strap kit Under seat bag Highfield dry bag Foot pump, oars, repair kit

* boat only

OPTIONAL EXTRAS

FRP Bow Step Molded bow cleat Bow cushion Boat cover

| (OLOVR SCHEMES | |
|---------------------------|-----|
| $\bullet \bullet \bullet$ | |
| | |
| | EVA |

| | (1260 | | (1290 | |
|------------------------|-------|--------|-------|---------|
| OVERALL LENGTH | 260cm | 8′6″ | 290cm | 9′6 |
| INTERNAL LENGTH | 176cm | 5′9″ | 206cm | 6'9″ |
| OVERALL WIDTH | 170cm | 5′7″ | 170cm | 5′7″ |
| INTERNAL WIDTH | 79cm | 2′7″ | 79cm | 2′7″ |
| DEADRISE | 15° | | 15° | |
| TUBE DIAMETER | 44cm | 17″ | 44cm | 17″ |
| NUMBER OF AIR CHAMBERS | 3 | | 3 | |
| MAXIMUM LOAD | 360kg | 794lbs | 480kg | 1058lbs |
| MAXIMUM PEOPLE | 3+1 | | 4 | |
| BOAT WEIGHT* | 54kg | 119lbs | 59kg | 130lbs |
| MAXIMUM POWER | 15hp | | 20hp | |
| ENGINE SHAFT | S | | S | |
| DESIGN CATEGORY | С | | С | |





THE COMPACT MODELS CAN CARRY 4 PEOPLE, MAKING THEM IDEAL FOR SHORT TRIPS. AGILE & STRONG OFFERING SLIGHTLY UP TO A 480KG PAYLOAD.

HEHRED

WGHFIELL

HH

Terr

HIGHFIELD